# 35mm Size Ring Type **EC35A Series**

## Thin-profile design with a 4.5mm body thickness and excellent operation feel.





Output signal: Two phase A and B

■ Ratings: 10mA 5V DC

Operating life: 50,000 cycles

Applications: Home: Office equipment

Audio\_TV:Visual

Automotive: Navigation/audio systems, HVAC

#### ■ Product List

Products No.	Actuator length (mm)	Detent torque	Number of detent	Number of pulse	Automotive	Drawing No.
EC35A1520402	20.0	18±7mN·m	30	15	•	1
EC35A0930401	20.0	22±8mN·m	18	9	•	2
EC35A1550502	25.0	30±15mN·m	30	15	•	3

### ⚠Note

- 1. This catalog shows only outline specifications. When using the products, please obtain formal specifications for supply.
- 2. Please place purchase orders per minimum order unit (integer).


### ■ Packing Specifications

Tray


Products No.	Number of packages(pcs.)		Export package measurements	
Floudota No.	1 case / Japan	1 case / export packing	(mm)	
EC35A1520402 EC35A0930401	420	840	540 x 360 x 380	
EC35A1550502	350	700	540 x 360 x 380	

### Drawing No.1

### ■ Dimensions



### ■ Mounting Hole Dimensions




Viewed from mounting side


# 35mm Size Ring Type **EC35A Series**

### Drawing No.2

### ■ Dimensions




### ■ Mounting Hole Dimensions




Viewed from mounting side

### Drawing No.3

### ■ Dimensions



### ■ Mounting Hole Dimensions



Viewed from mounting side