# Lever and Push Operation Type

## **SLLB Series**

### Compact, thin-profile horizontal type suitable for a wide range of applications.



- Directional resolution: 2-direction
- Ratings (max.)/(min.) (Resistive load): 10mA 5V DC/50µA 3V DC
- Operating temperature range: -40°C to +85°C

Applications: Audio\_TV: Cameras

#### ■ Product List

Products No.	Actuator configuration	Push-on switch	Operating force		Travel (Center push)	Location lug	Dimensions (W×D×H)	Automotivo	Drawing No.
			Lever portion	Push portion	(mm)	Location lug	(WADAH)	Automotive	Drawing No.
SLLB120100	Mounting knob	With	0.65±0.3N	2±1N	Refer to the dimensions	With	11.8×11.4×3.0	_	1
SLLB120200	Mounting knob integrated	With	0.65±0.3N	2±1N	Refer to the dimensions	With	11.8×11.4×3.0	_	2
SLLB120300	Mounting knob integrated	With	0.65±0.3N	2±1N	Refer to the dimensions	With	11.8×11.4×3.0	-	<u> </u>


#### ⚠Note

- 1. This catalog shows only outline specifications. When using the products, please obtain formal specifications for supply.
- 2. Please place purchase orders for taping products per minimum order unit (1 reel or a case).

#### ■ Packing Specifications


#### Taping

Numb	per of packages	(pcs.)	Tape width	Export package		
1 reel	1 case / Japan	1 case / export packing	(mm)	measurements (mm)		
1,350	2,700	5,400	24	428×413×172		




#### Drawing No.1

■ Dimensions




■ Land Dimensions



Viewed from mounting face.


■ Circuit Diagram




Push portion.

#### Drawing No.2


Dimensions



■ Land Dimensions



■ Circuit Diagram



Viewed from mounting face.

Push portion.