# Water-proof Lever Type SSCN Series

## Water-proof lever switch capable of left-right detection with a 40° operating angle per side.









- Rating(max.)/(min.)(Resistive load): 0.1A 12V DC/100µA 5V DC
- Contact resistance(Initial/After operating life):500mΩ max./1Ω max.
- Operating life without load: 100,000 cycles
- Operating life with load Rating(max.)(Resistive load):

100,000 cycles  $1\Omega$  max.

Applications: Energy\_Industrial: Robots, drones, Industrial equipment
Home: Major home appliances
Automotive: Hood Latch (Side/Rear/Door/Gear)

#### ■ Product List

Products No.	Poles	Positions	Operating force	Changeover timing	Terminal type	Dimensions (W×D×H) (mm)	Water-proof	Dust-proof	Automotive	Drawing No.
SSCN110101	1	2	2N max.	Non shorting	For PC board	5.0×13.0×15.0	•	•	•	1



- 1. This catalog shows only outline specifications. When using the products, please obtain formal specifications for supply.
- 2. This unit cannnot be used in water (IP6K7 rating, except for terminal).
- 3. Please place purchase orders per minimum order unit (integer).
- 4. This products can be used in vehicles.

Although these products are designed to perform over a wide operating temperature range, please ensure that you receive and read the formal delivery specifications before use.


#### ■ Packing Specifications

Tray

Number of pa	ckages(pcs.)	Export package measurements		
1 case / Japan	1 case / export packing	(mm)		
600	2,400	540 x 360 x 270		

### Drawing No.1

Dimensions



■ Circuit Diagram

