6.2×6.5mm (Surface Mount)

SKHM Series

Type with a height of 3.1 mm, including ground terminal options.



- Series type: Sharp feeling type
- Absolute Maximum Ratings: 50mA 12V DC
- ■Rating (min.):10µA 1V DC

Applications: Energy_Industrial: Industrial equipment

Home: Major home appliances, Office equipment

Audio_TV:Visual

■ Product List

Products No.	Operating direction	Operating force (N)	Travel (mm)	Operating life (cycles)	Initial contact resistance	Dimensions (W×D×H) (mm)	Water-proof	Dust-proof	Automotive	Drawing No.
SKHMQKK010	Top push	0.98	0.25	500,000	100mΩ max.	6.2×6.5×3.1	_	_	_	
SKHMQLK010	Top push	1.57	0.25	300,000	100mΩ max.	6.2×6.5×3.1	_	_	_	1
SKHMQMK010	Top push	2.35	0.25	200,000	100mΩ max.	6.2×6.5×3.1	_	_		


Note

- 1. This catalog shows only outline specifications. When using the products, please obtain formal specifications for supply.
- 2. Please place purchase orders for taping products per minimum order unit (1 reel or a case).

■ Packing Specifications


Taping

Numb	er of packages	(pcs.)	Tape width	Export package		
1 reel	1 case / Japan	1 case / export packing	(mm)	measurements (mm)		
3,000	24,000	24,000	16	395 x 395 x 205		




Drawing No.1

■ Dimensions



■ Land Dimensions



Viewed from switch mounting face

■ Circuit Diagram

