
5.2mm Square (Surface Mount)

SKQG Series

Automotive-compatible compact, thin-profile type with a height of 1.5mm.





Series type: Sharp feeling type

Absolute Maximum Ratings: 50mA 12V DC

■ Rating (min.): 10µA 1V DC

Applications: Mobile: Notebooks, peripherals

Healthcare: Healthcare equipment

Automotive: Remote Keyless Entry (RKE), Navigation/audio

systems, HVAC, Overhead consoles, Steering, Shifter

■ Product List

	Products No.	Operating direction	Operating force (N)	Travel (mm)	Operating life (cycles)	Initial contact resistance	Dimensions (W×D×H) (mm)	Water-proof	Dust-proof	Automotive	Drawing No.
	SKQGAFE010	Top push	0.98	0.25	500,000	100mΩ max.	5.2 x 5.2×1.5	_	_	•	
	SKQGABE010	Top push	1.57	0.25	1,000,000	100mΩ max.	5.2 x 5.2×1.5	_	_	•	
Ī	SKQGADE010	Top push	2.55	0.25	100,000	100mΩ max.	5.2 x 5.2×1.5	_	_	•	ı
	SKQGAKE020	Top push	3.43	0.25	100,000	100mΩ max.	5.2 x 5.2×1.5	_	_	•	


⚠Note

- 1. This catalog shows only outline specifications. When using the products, please obtain formal specifications for supply.
- 2. Please place purchase orders for taping products per minimum order unit (1 reel or a case).

■ Packing Specifications


Taping

Numb	er of packages	(pcs.)	Tape width	Export package measurements (mm)		
1 reel	1 case / Japan	1 case / export packing	(mm)			
4,000	40,000	40,000	12	395 x 395 x 205		




Drawing No.1


Dimensions



■ Land Dimensions



■ Circuit Diagram



Viewed from mounting face.