6.1×3.7mm (Surface Mount)

SKQY Series

High-speed mounting type with a height of 2.5mm, with ground terminal options.





■ Series type: Sharp feeling type

■ Absolute Maximum Ratings: 50mA 12V DC

■ Rating (min.): 10µA 1V DC

Applications:Energy_Industrial:Industrial equipment
Home:Office equipment

Automotive: Navigation/audio systems, HVAC, Overhead consoles, Steering

■ Product List

Products No.	Туре	Operating direction	Operating force (N)	Travel (mm)	Operating life (cycles)	Initial contact resistance	Dimensions (W×D×H) (mm)	Water-proof	Dust-proof	Automotive	Drawing No.
SKQYACE010	Top push type	Top push	0.98	0.25	50,000	500mΩ max.	6.1×3.7×2.5	_	_	•	- 1
SKQYAAE010		Top push	1.57	0.25	50,000	500mΩ max.	6.1×3.7×2.5	_	_	•	
SKQYABE010		Top push	2.55	0.25	50,000	500mΩ max.	6.1×3.7×2.5	_	_	•	
SKQYAFE010		Top push	3.14	0.25	50,000	500mΩ max.	6.1×3.7×2.5	_	_	•	
SKQYPCE010	With ground terminal type	Top push	0.98	0.25	50,000	500mΩ max.	6.1×3.7×2.5	_	_	•	- 2
SKQYPAE010		Top push	1.57	0.25	50,000	500mΩ max.	6.1×3.7×2.5	_	_	•	
SKQYPBE010		Top push	2.55	0.25	50,000	500mΩ max.	6.1×3.7×2.5	_	_	•	
SKQYPDE010		Top push	3.14	0.25	50,000	500mΩ max.	6.1×3.7×2.5	_	_	•	




- 1. This catalog shows only outline specifications. When using the products, please obtain formal specifications for supply.
- 2. Please place purchase orders for taping products per minimum order unit (1 reel or a case).

■ Packing Specifications

Taping


Numb	per of packages	(pcs.)	Tape width	Export package			
1 reel	1 case / Japan	1 case / export packing	(mm)	measurements (mm)			
3,000	30,000	30,000	12	395 x 395 x 205			




SKQY Series

Drawing No.1


■ Dimensions



■ Land Dimensions




■ Circuit Diagram




Viewed from mounting face.

Drawing No.2


■ Dimensions



■ Land Dimensions



■ Circuit Diagram



Viewed from mounting face.