
4.8mm Square (Surface Mount)

SKRB Series

Automotive-compatible compact, thin-profile type with a height of 0.55mm.





- Series type: Sharp feeling type
- Absolute Maximum Ratings: 50mA 12V DC
- Rating (min.): 10µA 1V DC

Applications: Home: Major home appliances, Office equipment
Automotive: Remote Keyless Entry (RKE), Navigation/audio
systems, HVAC, Overhead consoles, Steering, Shifter

■ Product List

| Products No. | Operating direction | Operating force (N) | Travel (mm) | Operating life (cycles) | Initial contact resistance | Dimensions (W×D×H) (mm) | Water-proof | Dust-proof | Automotive | Drawing No. |
|--------------|------------------------|------------------------|----------------|----------------------------|-------------------------------|-------------------------------|-------------|------------|------------|----------------|
| SKRBAGE010 | Top push | 1.1 | 0.15 | 2,000,000 | 100mΩ max. | 4.8×4.8×0.55 | _ | _ | • | |
| SKRBAAE010 | Top push | 1.57 | 0.2 | 1,000,000 | 100mΩ max. | 4.8×4.8×0.55 | _ | _ | • | 1 |
| SKRBACE010 | Top push | 2.55 | 0.2 | 500,000 | 100mΩ max. | 4.8×4.8×0.55 | _ | _ | • | 1 |
| SKRBAKE010 | Top push | 3.5 | 0.2 | 200,000 | 100mΩ max. | 4.8×4.8×0.55 | _ | _ | • | |


Note

- 1. This catalog shows only outline specifications. When using the products, please obtain formal specifications for supply.
- 2. Please place purchase orders for taping products per minimum order unit (1 reel or a case).

■ Packing Specifications


Taping

| Numb | er of packages | (pcs.) | Tape width | Export package | | |
|--------|----------------|----------------------------|------------|----------------------|--|--|
| 1 reel | 1 case / Japan | 1 case / export packing | (mm) | measurements (mm) | | |
| 10,000 | 100,000 | 100,000 | 12 | 395 x 395 x 205 | | |




Drawing No.1


■ Dimensions



■ Land Dimensions



■ Circuit Diagram



Viewed from mounting face.