4.5×3.4mm Side Push (Surface Mount)

SKRT Series

Side-push type with excellent soldering strength and good operation feel.



- Series type: Sharp feeling type
- Absolute Maximum Ratings: 50mA 12V DC
- ■Rating (min.): 10µA 1V DC

Applications: Mobile: Headsets, wearables

■ Product List

Products No.	Operating direction	Operating force (N)	Travel (mm)	Operating life (cycles)	Initial contact resistance	Guide bosses	Dimensions (W×D×H) (mm)	Water-proof	Dust-proof	Automotive	Drawing No.
SKRTLAE010	Side push	1.6	0.2	100,000	500mΩ max.	With	4.5×3.4×3.3	_	_	-	1
SKRTLBE010	Side push	1.6	0.2	100,000	500mΩ max.	Without	4.5×3.4×3.3	_	_	-	2


⚠Note

- 1. This catalog shows only outline specifications. When using the products, please obtain formal specifications for supply.
- 2. Please place purchase orders for taping products per minimum order unit (1 reel or a case).

■ Packing Specifications


Taping

Numb	er of packages	(pcs.)	Tape width	Export package			
1 reel 1 case / .		1 case / export packing	(mm)	measurements (mm)			
3,000	30,000	30,000	12	395 x 395 x 205			




Drawing No.1


■ Dimensions



■ Land Dimensions




■Circuit Diagram




Viewed from switch mounting face

Drawing No.2


Dimensions



■ Land Dimensions



■ Circuit Diagram



Viewed from switch mounting face