4.8×3.25mm Side Push (Surface Mount)

SKSJ Series

Long-life half-mount type with excellent soldering strength, capable of 1 million operation cycles.



- Series type: Sharp feeling type
- Absolute Maximum Ratings: 50mA 12V DC
- ■Rating (min.):10µA 1V DC

Applications: Mobile: Notebooks, peripherals, Headsets, wearables

Game:Home handheld consoles

Mobile:Headsets, wearables

Healthcare:Healthcare equipment

■ Product List

Product	ts No.	Operating direction	Operating force (N)	Travel (mm)	Operating life (cycles)	Initial contact resistance	Dimensions (W×D×H) (mm)	Water-proof	Dust-proof	Automotive	Drawing No.
SKSJLE	EE010	Side push	1.6	0.2	1,000,000	500mΩ max.	4.8×3.25×3.3	_	_	_	1


⚠Note

- 1. This catalog shows only outline specifications. When using the products, please obtain formal specifications for supply.
- 2. Please place purchase orders for taping products per minimum order unit (1 reel or a case).

■ Packing Specifications


Taping

Numb	er of packages	(pcs.)	Tape width	Export package		
1 reel	1 case / Japan	1 case / export packing	(mm)	measurements (mm)		
3,000	30,000	30,000	12	395 x 395 x 205		




Drawing No.1

Dimensions



■ Land Dimensions



Viewed from switch mounting face

■ Circuit Diagram

