3.9×2.9mm Side Push (Surface Mount)

SKTD Series

Type with a height of 1.55mm, compliant with IP6X equivalent/IPX7.







Series type: Sharp feeling type

Absolute Maximum Ratings: 50mA 12V DC

■ Rating (min.): 10µA 1V DC

Applications: Mobile: Smartphones, tablets, Headsets, wearables,
Notebooks, peripherals
Healthcare: Healthcare equipment

■ Product List

Products No.	Operating direction	Operating force (N)	Travel (mm)	Operating life (cycles)	Initial contact resistance	Dimensions (W×D×H) (mm)	Water-proof	Dust-proof	Water-proof & Dust-proof	Automotive	Drawing No.
SKTDLDE010	Side push	1.6	0.15	200,000	500m $Ω$ max.	3.9×2.9×1.55	•	•	IP6X equivalent/IPX7	_	1
SKTDLGE010	Side push	2.0	0.15	200,000	500mΩ max.	3.9×2.9×1.55	•	•	IP6X equivalent/IPX7	_	'

⚠Note

- 1. This catalog shows only outline specifications. When using the products, please obtain formal specifications for supply.
- 2. Please place purchase orders for taping products per minimum order unit (1 reel or a case).
- 3. Protective structure:


Assumes the switch is left alone without being operated. Under the specified conditions, dust and water ingress with a significant impact on the switch's on-off function is prevented.

IP6X equivalent/IPX7 dust and water resistance is guaranteed for the switch alone and performance may not be guaranteed depending on the mounting conditions and usage.

■ Packing Specifications


Taping

Numl	per of packages	(pcs.)	Tape width	Export package		
1 reel	1 case / Japan	1 case / export packing	(mm)	measurements (mm)		
4,500	45,000	45,000	12	395 x 395 x 205		




Drawing No.1


■ Dimensions



■ Land Dimensions



■ Circuit Diagram



Viewed from switch mounting face